



Global-Mark.com.au®



Material Safety Data Sheet

Issued:

1st June 2016

IDENTIFICATION

Product Name: **AUSPERL EXPANDED PERLITE**
Other Names: P100, P200, P400, P500 & P550
Product Use: Horticulture, insulation, construction and filler applications

PHYSICAL DATA

Appearance: Off-white, odourless, free flowing powder
Melting Point: Approx. 1250c
Boiling Point: Not applicable
Vapor Pressure: Not applicable
Specific Gravity: 200-250kg/m³
Flash Point: Not applicable
Flamm. Limit LEL: Not applicable
Explosion Data: Not applicable

OTHER PROPERTIES

Description: Perlite is essentially an amorphous, hydrated glassy volcanic rock of rhyolitic composition, consisting primarily of fused sodium potassium aluminium silicate.

Form: Powder

Ingredients:

Name	CAS Proportion
Perlite ore:	93763-70- 3; greater than 99.9%
Crystalline silica:	14464-46- 1; less than 0.1%
Cristobalite quartz:	14808-60- 1; less than 0.1%

HEALTH HAZARD INFORMATION

Acute – Ingestion: No adverse effects expected.
Acute – Eye: Exposure to the dust may cause discomfort due to the particulate nature.
Acute – Skin: Not expected to be a skin irritant.
Acute – Inhalation: Inhalation of dust may result in respiratory irritation.

FIRST AID

Ingestion: Rinse mouth with water - give plenty of water to drink. If vomiting occurs give further water. Seek medical advice.
Eye: Irrigate with copious quantities of water for 15 minutes. In all cases of eye contamination it is a sensible precaution to seek medical advice.
Skin: Wash contaminated skin with plenty of soap and water. If irritation occurs seek medical advice. Remove victim from exposure - avoid becoming a casualty.
Inhalation: Remove contaminated clothing and loosen remaining clothing. Patient to assume most comfortable position and kept at rest until fully recovered.
Advice to Doctor: Treat symptomatically.

AUSPERL PTY LTD

Tel: +61 2 8318 7824 • Fax: +61 2 9791 1350 • Email: info@ausperl.com.au
PO Box 381 Padstow, NSW 2211 • 64 Gow Street, Padstow, NSW 2211
ACN: 605 415 816 • ABN: 39 605 415 816 • www.ausperl.com.au

Ausperl



Global-Mark.com.au®



PRECAUTIONS FOR USE

Exposure Limits:

OSHA PEL - 15 mg/m³
ACGIH TLV 10 mg/m³

Other Exposure Info:

No value assigned for this specific material by the Occupational Health & Safety Administration.

Engineering Controls:

Ensure ventilation is adequate to maintain air concentrations below exposure standard. Avoid generating and inhaling dust. Keep containers closed when not in use.

Protective Equipment:

No specific safety equipment required. Preferable to avoid skin and eye contact and inhalation of dust. Wear overalls, safety glasses and impervious gloves. Avoid generating and inhaling dust. If dust exists, wear dust mask/respirator meeting the requirements of AS1715 and AS1716. Always wash hands before eating, drinking or using the toilet.

Fire Hazards:

Perlite is a fully oxidized non-flammable mineral. It is non-combustible.

REACTIVITY

Stability:

Stable

Incompatibility:

None (reacts with hydrofluoric acid; soluble in HF)

Hazardous Polymerization:

Will not occur

Conditions to avoid:

None

SAFE HANDLING INFORMATION

Storage Precautions:

Not defined as a Dangerous Good. Store in a dry place.

Spills and Leaks:

Use respirators suitable for nuisance dust & eye protection. Sweep up, but avoid generating dust.

Disposal:

Dispose in bulk or containerised according to local regulations. Normally approved for disposal at approved land waste sites.

OTHER INFORMATION

Toxicology: Inhaling crystalline silica-containing dust can aggravate upper respiratory conditions such as asthma or emphysema. Long term exposure to mineral dust which contains crystalline silica can cause the lung disease silicosis. A recent review by the International Agency for Research into Cancer of public literature on the carcinogenic risk of silica and silicates has concluded that there is limited evidence for the carcinogenicity of crystalline silica to humans.

CONTACT POINT

In the case of an emergency contact the Production Manager on (02) 8318 8724 or for additional information on this or other products contact by email (info@ausperl.com.au) This material safety data sheet and the information contained herein is provided for the sole purpose of enabling persons handling and using the product to do so with safety.

AUSPERL PTY LTD

Tel: +61 2 8318 7824 • Fax: +61 2 9791 1350 • Email: info@ausperl.com.au
PO Box 381 Padstow, NSW 2211 • 64 Gow Street, Padstow, NSW 2211
ACN: 605 415 816 • ABN: 39 605 415 816 • www.ausperl.com.au